

PROFILUX PLUS SYSTEM



PROFILUX
plus

UNIT • REFLECTOR NOT INCLUDED WITH SINGLE UNIT



PROPLUS-2*
multi-voltage flash unit, /mains-
and battery operated, 200 Ws



**PLUSROR/
PLUSROW**
flash tubes,
uncoated/coated



PROHAL
halogen tube,
70 W/
220-240 V



PROPLUS-4*
multi-voltage flash unit, /mains-
and battery operated, 400 Ws



**PLUSROR/
PLUSROW**
flash tubes,
uncoated/coated



LUHAL-2
halogen tube,
150 W/
220-240 V



PROPLUS-6*
multi-voltage flash unit, /mains-
and battery operated, 600 Ws



**PLUSROR/
PLUSREW**
flash tube,
uncoated/coated



LUHAL-3
halogen tube,
200 W/
220-240 V



VANET
power
cable,
5 m



MASYG
sync
lead



COMKAP
protection
cap

110 V-130 V OPERATION



PACHAL
halogen tube,
150 W/110-130 V



PLUSKLA
pyrex dome

BATTERY PACK



PAC-1
battery pack
for 2 Profilux Plus units,
8,8 kg, capacity:
Over 1400 flashes



PAC-2
battery pack
for 2 Profilux Plus units,
12 kg, capacity:
Over 3200 flashes



PACLA
multi-voltage
charger



PACLNET
lamp cable,
PROPAC to
PROPLUS, 5 m



PACLA 12
12 V. charger



TRAPLUG
travel plug
adapter



PACNET E
extension cable,
for PACNET, 3 m




PACHAL*
halogen tube,
150 W/110-130 V



PLUSKLA*
pyrex dome

* USE FOR BATTERY OPERATION

OCTOBOKES AND SOFTBOXES



PROFOC-120-R
Octobox
(Recessed),
Ø 120 cm,
honeycomb
insert
available
separately



PROFOC-150
Octobox,
Ø 150 cm



PROFEX-80
75 x 75 cm




FEXWAN-80



PROREC-60
60 x 100 cm



PROWAN-30
30 x 120 cm



PROFLAP-60/-80/-100:
Creative Kits, PROFLAP-60 for PROFEX-60
PROFLAP-80 for PROFEX-80
PROFLAP-100 for PROFEX-100



COMFEX-40
40 x 40 cm



PROFEX-60
60 x 60 cm



TEXWAB-60

ELECTRONIC ACCESSORIES



MURAS-T
radio trigger



MUSEN
IR trigger



PLUSTEN
antenna for
Profilux Plus,
increases receiver
range from
approx. 30 m
to approx. 60 m

REFLECTORS, GELS & GRIDS



UMBRELLAS

